

SPECIFICATION

Flow rates	1 GPM (3.8 LPM) bottle fill 4 GPM (15.2 LPM) bucket fill 1 GPM (3.8 LPM) bucket fill
Back flow preventer	Flex-gap
Temperature	Max: 140° F (60° C)
Ideal operating pressure	40-50 PSI (2.8 - 3.5 bar)
Minimum Pressure	20 PSI (1.4 bar)
Maximum Pressure	100 PSI (6.9 bar)


MATERIAL SPECIFICATION

Cover	ABS
Flex-gap	Polypropylene
O-ring	EPDM
Water Valve	Acetal
Water Inlet	Brass

INSTALLATION

Mounting the unit

- (1) Choose a convenient location close to water supply and not more than 5' off floor.
- (2) Remove the cover of the unit as two of the mounting holes are behind the cover.
- (3) Hold proportioner against wall and mark keyholes — use a level for marking holes.
- (4) Drill holes and install either toggle bolts or masonry screws (not supplied).
- (5) Hang the unit and tighten screws. Always refer to hardware manufacturer's specifications for weight capacity and usage.
- (6) When reattaching the cover, be sure that the button lines up properly with the dial. There is a groove in shaft of the button on the large end that should line up with a raised ridge on the dial so that the cover can only be put on one way.



Attaching the drip tray (optional)

- (1) Locate tray 12" to 15" below spouts. Mount in the same manner as proportioner.
- (2) Attach a length of 1/4" tubing to drip tray for draining liquids.
- (3) Divert drain tube to sink, drain, or five gallon holding jug.

Connecting the water supply

This proportioner operates best with a flowing water pressure of 40 - 50 PSI. If water pressure exceeds 50 PSI, Knight recommends using a 45 PSI fixed pressure regulator (P/N 7407117). Fluctuating pressure can affect dilution ratios — use a water source that is not feeding other equipment whenever possible. Water temperature should be between 40°F and 140°F.

- (1) Attach male connector on high pressure supply hose to inlet side of proportioner using a garden hose washer. Water inlet can be located on the left side if necessary.
- (2) Attach female connector on high pressure hose to water source.
- (3) Turn on water and check for possible leaks.

IMPORTANT NOTE:

If proportioner is connected to a janitor's sink with an atmospheric vacuum breaker, a special connection kit is required by A.S.S.E. specification 1055. Failure to use this kit, or equivalent connection means, will invalidate the A.S.S.E. and I.A.P.M.O. (UPC) certification. Specify P/N 7600187 when ordering the kit.



CAUTION: Wear protective clothing and eyewear when dispensing chemicals or other materials. Observe safety handling instructions (MSDS) of chemical mfrs.



CAUTION: When installing any equipment, ensure that all national and local safety and plumbing codes are met.

OPERATION

Connecting the chemical supply

- (1) Locate chemical container(s) below the proportioner.
- (2) Insert the foot-valve end of the 3/8" vinyl tube into each container (use ceramic weight if necessary to sink tube to bottom).
- (3) Connect the inlet tube over the colored metering tip — secure with a plastic zip tie.

Installing bucket-fill or bottle fill tube (optional)

- (1) Connect the bucket or bottle fill tube with the flow restrictor (plastic insert) end closest to the venturi body.
- (2) Secure tube to venturi body with tie wraps provided.

Dispensing chemical-water mix

- (1) Select the desired product with the selector knob.
- (2) Press the button on the front cover—release button when container is full.
- (3) If desired, the button can be "locked" in the ON position for filling large containers such as mop buckets or floor scrubbers. Simply turn the button slightly clockwise when pressed in. To release, turn button counter-clockwise.

DIAL POSITION

The selector dial has 4 positions that correspond to the 4 chemical inlet ports (see figure below). Labels can be applied to the cover of the unit to identify where to point the dial for each particular chemical. When inserting metering tips, be sure to match up the correct tip for the chemical that will be used on each port.



CHOOSING DILUTION RATES

IMPORTANT: Be sure to use the correct dilution column for metering tip selection.

Metering tip selection

For each port in the system, install appropriate metering tip from the charts at the bottom of the page. Be sure the metering tip is threaded in hand-tight only.

Calibrating actual product ratios

To easily calculate the ounces per gallon for a specific product:

- (1) Fill a graduated cylinder or spray bottle (that has ounce markings) with product.
- (2) Install metering tip closest to desired ounces per gallon — see dilution charts.
- (3) Drop chemical pick-up tube into the container holding the product.
- (4) Activate valve until chemical line is primed up to the metering tip.
- (5) Note how many ounces (of product) are in the container.
- (6) Activate valve again, and fill a one gallon container with water/product mix.
- (7) Note how many ounces (of product) were used.
- (8) You now have determined actual ounces per gallon for this product.

METERING TIP CHART				
	1 GPM		4 GPM	
TIP COLOR	OZ/GAL	RATIO	OZ/GAL	RATIO
NO INSERT	28	3.6:1	25	4.3:1
WHITE	22	4.8:1	20	5.4:1
YELLOW	18	6.1:1	18	6.1:1
PINK	16	7.0:1	16	7.0:1
GREEN	15	7.8:1	12	12:1
BLACK	14	8.5:1	10	15:1
BROWN	12	10:1	7	20:1
GRAY	8	15:1	5	31:1
BLUE	6	20:1	4	42:1
RED	3	42:1	3	63:1
PEACH	2.5	50:1	2	72:1
LT BLUE	2.0	63:1	1.5	101:1
PURPLE	1.75	74:1	1	127:1
LT GREEN	1.5	84:1	0.75	170:1
ORANGE	1	127:1	0.50	255:1
LT BROWN	0.5	255:1	0.25	511:1

This chart is based upon the chemical viscosity of water (CPS = 1.0) and should only be used as a guide. Actual ratios and flow rates may vary due to product viscosity, flow pressure, and tubing distance.

CONNECTING MULTIPLE UNITS

- Multiple units can be connected side by side for any configuration that is required (example—below left).
- Connected units can be mounted using the optional joggle bracket (example—below right).
- Water inlet connection can be relocated from right to left side if necessary by following the steps below.
 - (1) Remove the brass inlet fitting from the right side by turning it counter-clockwise with a pair of pliers.
 - (2) Remove the plastic plug from the left side by turning it counter-clockwise with an 11/16" wrench.
 - (3) Thread the brass inlet fitting into the left side by turning it clockwise until hand-tight, then go 1/4 turn with the pliers.
 - (4) Thread the plastic plug into the right side by turning it clockwise until hand-tight, then go a 1/4 turn with the wrench.



CHOOSING THE FLOW RATE

The flow rate is controlled by a venturi tube located within the venturi body. Venturi tubes have their GPM rating molded on the side, or can be identified by color; WHITE = 1 GPM/ BLACK = 4 GPM.

To change the venturi tube:

- (1) Remove the cover by gently snapping it away from the unit.
- (2) Disconnect tubing from venturi body.
- (3) Twist the venturi body counter-clockwise to remove it from the water valve.
- (4) Push out existing venturi tube by inserting a pen up through the bottom of the venturi body (note the order of the parts as they are removed from the flex-gap/venturi body).
- (5) Insert the new venturi tube (for the desired flow rate) into the venturi body, ensuring that it seats firmly. Replace the flex-gap parts in the order removed from the previous step.
- (6) Twist the venturi body clockwise to reattach it to the water valve.

SAFETY AND SERVICING TIPS

- Avoid direct contact with chemicals — handle containers with caution. To avoid spillage, be careful not to tip containers.
- Insert chemical suction line into container so that footvalve and ceramic weight sink to the bottom.
- If valve fails to draw chemical, check the metering tip and footvalve for blockage — soak in warm water to clear.

FLEX-GAP ANNUAL CLEANING AND TEST PROCEDURES FOR UNITS INSTALLED IN CANADA

Each year, your chemical dispenser must be cleaned and its backflow prevention performance verified. As this device is an end-of-line device (versus an in-line device) and evidence of effective backflow prevention is determined visually, a two-minute pressure test is not necessary.

If the Flex-Gap device cannot readily be seen during the test procedure, the housing of the chemical dispensing unit must be removed during testing. Apply the appropriate test procedure below as applicable for your chemical dispensing unit.

4 GPM VENTURIS

1. Fill discharge hose with water by opening the valve.
2. When water begins to exit the discharge hose turn off the water and raise the end of the hose above the Flex-Gap.
3. Observe that water is exiting the Flex-Gap.
4. If the water is exiting the Flex-Gap it has passed the test.
5. If the water is not exiting from the Flex-Gap, replace the Flex-Gap sleeve as per the instruction manual and re-test.
6. If the water is not exiting from the Flex-Gap after replacing the sleeve and re-testing, replace the complete Flex-Gap assembly and re-test.
7. If the water is not exiting from the Flex-Gap after replacing the Flex-Gap assembly, disconnect the water supply and replace the complete unit.





1 GPM VENTURIS

1. Remove the Fill Tube Spout and replace with a 4-foot length of 1/2" ID hose.
2. Fill the discharge hose with water by opening the valve.
3. When water begins to exit the discharge hose, turn off the water and raise the end of the hose above the Flex-Gap.
4. Observe that water is exiting the Flex-Gap.
5. If the water is exiting the Flex-Gap, it has passed the test.
6. If the water is not exiting from the Flex-Gap, replace the Flex-Gap sleeve and re-test.
7. If the water is not exiting from the Flex-Gap after replacing the sleeve and re-testing, replace the complete Flex-Gap assembly and re-test.
8. If the water is not exiting from the Flex-Gap after replacing the Flex-Gap assembly, disconnect the water supply and replace the complete unit.

ACCESSORY KIT PARTS (NOT SHOWN)

PART NUMBER	DESCRIPTION	QTY
0300519	Ceramic Tube Weight	4
0901148	Manual	1
7026905	Tube Assy, Discharge w/Restrictor	1
2201200	Metering tip kit with chart	2
2201225	Umbrella Valve	4
7025842	Tube, T-38V Vinyl 1/4" ID x 3/8" OD 6 ft.	4
7600121	Mounting Kit w/ #10 Screws and anchors - 2 ea	2

PARTS DIAGRAM



NOTES

DISCLAIMER

Knight LLC does not accept responsibility for the mishandling, misuse, or non-performance of the described items when used for purposes other than those specified in the instructions. For hazardous materials information consult label, MSDS, or Knight LLC. Knight products are not for use in potentially explosive environments. Any use of our equipment in such an environment is at the risk of the user, Knight does not accept any liability in such circumstances.

WARRANTY

All Knight controls and pump systems are warranted against defects in material and workmanship for a period of ONE year. All electronic control boards have a TWO year warranty. Warranty applies only to the replacement or repair of such parts when returned to factory with a Knight Return Authorization (KRA) number, freight prepaid, and found to be defective upon factory authorized inspection. Bearings and pump seals or rubber and synthetic rubber parts such as "O" rings, diaphragms, squeeze tubing, and gaskets are considered expendable and are not covered under warranty. Warranty does not cover liability resulting from performance of this equipment nor the labor to replace this equipment. Product abuse or misuse voids warranty.

FOOTNOTE

The information and specifications included in this publication were in effect at the time of approval for printing. Knight LLC reserves the right, however, to discontinue or change specifications or design at any time without notice and without incurring any obligation whatsoever.

KNIGHT LLC (www.knightequip.com)

Knight Headquarters Tel: 949.595.4800 Fax: 949.595.4801	USA Toll Free Tel: 800.854.3764 Fax: 800.752.9518	Knight Canada Tel: 905.542.2333 Fax: 905.542.1536	Knight Europe Tel: 0044.1323.514855 Fax: 0044.1323.514828	Knight Australia Tel: 61.02.9352.1801 Fax: 61.02.9352.1899	Knight N. Asia Tel: 82.2.3481.6683 Fax: 82.2.3482.5742	Knight S. Asia Tel: 65.6763.6633 Fax: 65.6489.6723
--	--	--	--	---	---	---